



Rim-/tire-width and pressure specifications

Table 1 Tubeless

max pressure bar/psi		rim inner width									
WITH HOOK		18mm	19mm	20mm	21mm	22mm	23mm	24mm	25mm	30mm	
tire width		Streem R.50 Streem R.66 Streem R.80	Streem R.38	Performance R.32	Advanced R.42	Streem C.35/C.38 Streem S.60/S.66 Streem TT.80	Advanced A.50	Streem A.49 Streem A.54	Performance 25	Beskar 30 Forge 30 Performance 30	
23mm	0.90"	8,5	8,5	8,5	8,5	8,3	8,1				
25mm	1.00"	8,0	8,0	8,0	8,0	7,8	7,6	7,4			
28mm	1.10"	7,5	7,5	7,5	7,5	7,3	7,1	6,9	6,7		
30mm	1.20"	7,0	7,0	7,0	7,0	6,8	6,6	6,4	6,2		
32mm	1.25"	6,5	6,5	6,5	6,5	6,3	6,1	5,9	5,7		
33mm	1.30"	6,1	6,1	6,1	6,1	5,9	5,7	5,5	5,3		
35mm	1.40"	5,6	5,6	5,6	5,6	5,4	5,2	5,0	4,8		
38mm	1.50"	5,3	5,3	5,3	5,3	5,1	4,9	4,7	4,5		
40mm	1.60"	5,0	5,0	5,0	5,0	4,8	4,6	4,4	4,2	4,0	
45mm	1.80"	4,8	4,8	4,8	4,8	4,6	4,4	4,2	4,0	3,8	
50mm	2.0"	4,6	4,6	4,6	4,6	4,4	4,2	4,0	3,8	3,6	
53mm	2.1"		4,5	4,5	4,5	4,3	4,1	3,9	3,7	3,5	
55mm	2.2"			4,4	4,4	4,2	4,0	3,8	3,6	3,4	
58mm	2.3"				4,3	4,1	3,9	3,7	3,5	3,3	
61mm	2.4"					4,0	3,8	3,6	3,4	3,2	
63mm	2.5"						3,7	3,5	3,3	3,1	
66mm	2.6"							3,4	3,2	3,0	
68mm	2.7"								3,1	2,9	
71mm	2.8"									2,8	
76mm	3.0"										

ideal tire/rim width combination

possible combination

DO NOT EXCEED THE MAX. PRESSURE STATED ON THE RIM / TIRE

max pressure bar/psi		24mm/25mm		30mm
HOOKLESS		Advanced G.34 Evolution X.R.25 Advanced X.R.25/36		Phase 30 Evolution A.30 Evolution E.G.30
tire width				
23mm	0.90"			
25mm	1.00"			
28mm	1.10"			
30mm	1.20"			
32mm	1.25"		4,0	
33mm	1.30"		4,0	
35mm	1.40"		4,0	
38mm	1.50"		4,0	
40mm	1.60"		4,0	
45mm	1.80"		3,5	
50mm	2.0"		3,5	3,0
53mm	2.1"		3,3	3,0
55mm	2.2"		3,1	3,0
58mm	2.3"		2,9	2,9
61mm	2.4"		2,7	2,7
63mm	2.5"		2,6	2,6
66mm	2.6"			2,5
68mm	2.7"			2,4
71mm	2.8"			2,3
76mm	3.0"			

Table 2 Tube Type

max pressure bar/psi		rim inner width									
WITH HOOK		18mm	19mm	20mm	21mm	22mm	23mm	24mm	25mm	30mm	
tire width		Streem R.50 Streem R.66 Streem R.80	Streem R.38	Performance R.32	Advanced R.42	Streem C.35/C.38 Streem S.60/S.66 Streem TT.80	Advanced A.50	Streem A.49 Streem A.54	Performance 25	Beskar 30 Forge 30 Performance 30	
23mm	0.90"	8,5	8,5	8,5	8,5	8,3	8,1				
25mm	1.00"	8,5	8,5	8,5	8,5	8,3	8,2	8,0			
28mm	1.10"	8,0	8,0	8,0	8,0	7,8	7,6	7,4	7,3		
30mm	1.20"	7,5	7,5	7,5	7,5	7,3	7,1	6,9	6,8		
32mm	1.25"	7,0	7,0	7,0	7,0	6,8	6,6	6,4	6,5		
33mm	1.30"	6,5	6,5	6,5	6,5	6,3	6,1	5,9	6,0		
35mm	1.40"	6,1	6,1	6,1	6,1	5,9	5,7	5,5	5,4		
38mm	1.50"	5,7	5,7	5,7	5,7	5,5	5,3	5,1	5,0		
40mm	1.60"	5,5	5,5	5,5	5,5	5,3	5,1	4,9	4,8	4,7	
45mm	1.80"	5,3	5,3	5,3	5,3	5,1	4,9	4,7	4,6	4,5	
50mm	2.0"	5,1	5,1	5,1	5,1	4,9	4,7	4,5	4,4	4,3	
53mm	2.1"		5,0	5,0	5,0	4,8	4,6	4,4	4,3	4,2	
55mm	2.2"			4,9	4,9	4,7	4,5	4,3	4,2	4,1	
58mm	2.3"				4,8	4,6	4,4	4,2	4,1	4,0	
61mm	2.4"					4,0	3,8	3,6	3,5	3,5	
63mm	2.5"						3,7	3,5	3,3	3,3	
66mm	2.6"							3,4	3,1	3,1	
68mm	2.7"								2,9	2,9	
71mm	2.8"									2,8	
76mm	3.0"										

ideal tire/rim width combination

possible combination

DO NOT EXCEED THE MAX. PRESSURE STATED ON THE RIM / TIRE

max pressure bar/psi		24mm/25mm		30mm
HOOKLESS		Advanced G.34 Evolution X.R.25 Advanced X.R.25/36		Phase 30 Evolution A.30 Evolution E.G.30
tire width				
23mm	0.90"			
25mm	1.00"			
28mm	1.10"			
30mm	1.20"			
32mm	1.25"		4,3	
33mm	1.30"		4,3	
35mm	1.40"		4,3	
38mm	1.50"		4,3	
40mm	1.60"		4,3	
45mm	1.80"		3,8	
50mm	2.0"		3,8	3,3
53mm	2.1"		3,6	3,3
55mm	2.2"		3,4	3,3
58mm	2.3"		3,2	3,2
61mm	2.4"		3,0	3,0
63mm	2.5"		2,9	2,9
66mm	2.6"			2,8
68mm	2.7"			2,7
71mm	2.8"			2,6
76mm	3.0"			